

Material Safety Data Sheet

Material: 60002680

WACKER® AK 35
SILICONE FLUID

Version: 1.2 (US)

Date of print: 01/25/2013

Date of last alteration: 12/20/2012

1. Product and company identification

1.1 Identification of the substance or preparation:

Commercial product name: **WACKER® AK 35**
SILICONE FLUID

Use of substance / preparation: Industrial.
Intermediate chemical

1.2 Company/undertaking identification:

Manufacturer/distributor: Wacker Chemie AG
Hanns-Seidel-Platz 4
81737 München
Germany

Customer information: Wacker Chemical Corporation
3301 Sutton Road
Adrian, Michigan 49221-9397
USA
InfoLine:
Tel (517) 264-8240, Fax (517) 264-8740
Hours of operation:
Monday - Friday, 8 am to 5 pm (eastern standard time)
Corporate website: www.wacker.com

Emergency telephone no. (24h): (517) 264-8500
Transportation emergency: (800) 424-9300 (CHEMTREC, USA)
(703) 527-3887 (CHEMTREC, international)

This MSDS was prepared by the Regulatory Affairs and Product Safety Department (RAPS) of Wacker Chemical Corporation.

2. Composition/information on ingredients

2.1 Chemical characterization (substance)

Chemical characteristics

Polydimethylsiloxane

2.2 Information on ingredients:

Type	CAS No.	Substance	Content [wt. %]		Note
			Lower	Upper	
INHA	63148-62-9	Polydimethyl siloxane	60.0	100.0	NH

Type: HYD - by-product upon hydrolysis, INHA - ingredient, NEBE - by-product, MONO - residual monomer, VERU - impurity, VUL - by-product upon vulcanization. *** **Note:** C1 - IARC carcinogen, C2 - NTP carcinogen, C3 - OSHA carcinogen, NH - non-hazardous, R - reproductive toxin.

This material does not contain any hazardous substances at or above OSHA and WHMIS reportable levels.

Substances listed in the Subsections "HAPS" and "California Proposition 65 Carcinogens / Reproductive Toxins" that are not listed in Section 2 are only present at quantities below 0.1% for California Proposition 65 listed toxins or below 1% for non-carcinogenic HAPS or they are inextricably bound in the product.

3. Hazards identification

3.1 Hazards classifications

HMIS® rating (product as packaged):

Health: 1

Fire: 1

Reactivity: 0

PPE: B

(HMIS codes are based on contact with the product as packaged and any hydrolysis by-products, if present.) Hazardous Materials Identification System and HMIS are registered trademarks of the National Paint and Coatings Association.

Material Safety Data Sheet

Material: 60002680

WACKER® AK 35
SILICONE FLUID

Version: 1.2 (US)

Date of print: 01/25/2013

Date of last alteration: 12/20/2012

Canadian WHMIS Classification: D2A

3.2 Emergency overview and potential hazards

This material is not hazardous under OSHA criteria. This material is not hazardous under WHMIS criteria. Liquid silicone based materials have lubricating properties that can substantially reduce or eliminate traction and may pose a slip hazard. Please use warning labels on consumer products where traction is essential for safety.

Physical Hazards:

No known physical hazards.

Acute health effects**Route of entry or possible contact:**

eyes , skin , inhalation (aerosol) , ingestion .

Eye contact:

May cause slight eye irritation.

Skin contact:

No acute toxic effects are expected.

Inhalation:

No acute toxic effects are known.

Ingestion:

Not expected in industrial use.

Additional information on acute health effects:

The toxicological evaluation is based on test results with a similar product.

3.3 Further information:

Chronic health effects:

No known or expected chronic health effects.

Medical conditions which may be aggravated by exposure:

none known

Carcinogens/Reproductive toxins:

There are no carcinogenic ingredients present at or over 0.1% in this material. This material does not contain any reproductive toxins at or above OSHA or WHMIS reportable levels.

See Section 11 for Toxicological Information, if any.

4. First-aid measures

4.1 General information:

Get medical attention if irritation or other symptoms occur. Before seeking medical attention remove contaminated clothing and shoes. Take a copy of the Safety Data Sheet when going for medical treatment.

4.2 After inhalation

Material cannot be inhaled under normal conditions.

4.3 After contact with the skin

For skin contact, immediately wipe away excess material. Use a waterless hand cleaner to remove as much of the remaining material as possible. Wash with soap and water.

4.4 After contact with the eyes

If contact with eyes, immediately hold eyelids apart and flush with plenty of water for at least 15 min.

4.5 After swallowing

After swallowing No special treatment is required.

4.6 Advice for the physician

Treat symptomatically.

5. Fire-fighting measures

Material Safety Data Sheet

Material: 60002680

WACKER® AK 35
SILICONE FLUID

Version: 1.2 (US)

Date of print: 01/25/2013

Date of last alteration: 12/20/2012

5.1 Flammable properties:

Property:	Value:	Method:
Flash point.....	270 °C (518 °F)	(ISO 2592)
Flash point.....	> 120 °C (> 248 °F)	(EN 22719)
Boiling point / boiling range	> 200 °C (> 392 °F) at 0.5 hPa	
Lower explosion limit (LEL)	not applicable	
Upper explosion limit (UEL).....	not applicable	
Ignition temperature	approx. 400 °C (752 °F)	(DIN 51794)

5.2 Fire and explosion hazards:

This material does not present any unusual fire or explosion hazards.

5.3 Recommended extinguishing media:

water-mist , carbon dioxide , sand , dry chemical or alcohol-resistant foam .

5.4 Unsuitable extinguishing media:

water-spray , sharp water jet .

5.5 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

-

5.6 Fire fighting procedures:

Fire fighters should wear full protective clothing including a self-contained breathing apparatus. Cool endangered containers with water.

6. Accidental release measures

6.1 Precautions:

If material is released indicate risk of slipping. Do not walk through spilled material.

HAZWOPER PPE Level: D

6.2 Containment:

Prevent material from entering surface waters, drains or sewers and soil. Contain any fluid that runs out using suitable material (e.g. earth). Close leak if possible without risk.

Spills of material which could reach surface waters must be reported to the United States Coast Guard National Response Center's toll free phone number (800) 424-8802.

6.3 Methods for cleaning up

Take up mechanically and dispose of according to local/state/federal regulations. For small amounts: Absorb with a liquid binding material such as diatomaceous earth and dispose of according to local/state/federal regulations. Contain larger amounts and pump up into suitable containers. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Apply sand or other inert granular material to improve traction.

7. Handling and storage

7.1 General information:

No special protective measures required.

7.2 Handling

Precautions for safe handling:

Spilled substance increases risk of slipping.

Precautions against fire and explosion:

Observe the general rules for fire prevention.

7.3 Storage

Conditions for storage rooms and vessels:

none known

Material Safety Data Sheet

Material: 60002680

WACKER® AK 35
SILICONE FLUID

Version: 1.2 (US)

Date of print: 01/25/2013

Date of last alteration: 12/20/2012

Advice for storage of incompatible materials:
not applicable

Further information for storage:
Keep container tightly closed. Store in a dry and cool place.

8. Exposure controls and personal protection

8.1 Engineering controls

Ventilation:

Use with adequate ventilation.

Local exhaust:

No special ventilation required.

8.2 Associate substances with specific control parameters such as limit values

-

Further information:

Maximum concentration at workplace recommended by producer: octamethylcyclotetrasiloxane (D4, CAS no. 556-67-2) = 10 ppm (123 mg/m³) .

8.3 Personal protection equipment (PPE)

Respiratory protection:

Respiratory protection is not normally required.

Hand protection:

Any liquid-tight rubber or vinyl gloves.

Eye protection:

Safety glasses with side shields or chemical safety goggles.

Other protective clothing or equipment:

Additional protective clothing or equipment is not normally required. Provide eye bath and safety shower.

8.4 General hygiene and protection measures:

Avoid contact with eyes, skin and clothing. Do not eat, drink or smoke when handling. Follow standard industrial hygiene practices when using this material. Wash thoroughly after handling.

9. Physical and chemical properties

9.1 Appearance

Physical state / form liquid
Colour colourless, clear
Odour odourless

9.2 Safety parameters

Property:	Value:	Method:
Melting point / melting range	-60 °C (-76 °F)	
Boiling point / boiling range	> 200 °C (> 392 °F) at 0.5 hPa	
Flash point.....	270 °C (518 °F)	(ISO 2592)
Flash point.....	> 120 °C (> 248 °F)	(EN 22719)
Ignition temperature	approx. 400 °C (752 °F)	(DIN 51794)
Lower explosion limit (LEL)	not applicable	
Upper explosion limit (UEL).....	not applicable	
Vapour pressure.....	< 0.1 hPa at 20 °C (68 °F)	
Density	approx. 0.96 g/cm ³ at 25 °C (77 °F)	(DIN 51757)
Water solubility / miscibility.....	virtually insoluble	
pH-Value	approx. 7	
Viscosity (dynamic)	31 - 39 mPa.s at 25 °C (77 °F)	(DIN 53019)
Viscosity (kinematic)	approx. 35 mm ² /s at 25 °C (77 °F)	(DIN 53019)

Material Safety Data Sheet

Material: 60002680

WACKER® AK 35
SILICONE FLUID

Version: 1.2 (US)

Date of print: 01/25/2013

Date of last alteration: 12/20/2012

9.3 Further information

Thermal decomposition: Decomposition begins at > 250 °C (> 482 °F)

10. Stability and reactivity

10.1 General information:

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

10.2 Conditions to avoid

none known

10.3 Materials to avoid

none known

10.4 Hazardous decomposition products

If stored and handled properly: none known . Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

10.5 Further information:

Hazardous polymerization cannot occur.

11. Toxicological information

11.1 Information on toxicological effects

Toxicological testing has been conducted with similar product(s).

11.1.1 Acute toxicity

Assessment:

Based on the available data acute toxic effects are not expected after single oral exposure. Based on the available data acute toxic effects are not expected after single dermal exposure.

Product details:

Route of exposure	Result/Effect	Species/Test system	Source
oral	LD ₅₀ : > 5000 mg/kg	rat	Conclusion by analogy
dermal	LD ₅₀ : > 2008 mg/kg	rat	Conclusion by analogy

11.1.2 Skin corrosion/irritation

Assessment:

Based on the available data a clinically relevant skin irritation hazard is not expected.

Product details:

Result/Effect	Species/Test system	Source
not irritating	rabbit	Conclusion by analogy

11.1.3 Serious eye damage / eye irritation

Assessment:

Based on the available data a clinically relevant eye irritation hazard is not expected.

Product details:

Result/Effect	Species/Test system	Source
not irritating	rabbit	Conclusion by analogy

Material Safety Data Sheet

Material: 60002680

WACKER® AK 35
SILICONE FLUID

Version: 1.2 (US)

Date of print: 01/25/2013

Date of last alteration: 12/20/2012

11.1.4 Respiratory or skin sensitization

Assessment:

Based on the available data a sensitization reaction is not expected from this product.

Product details:

Route of exposure	Result/Effect	Species/Test system	Source
dermal	not sensitizing	guinea-pig; Magnusson-Kligman	Conclusion by analogy OECD 406

11.1.5 Germ cell mutagenicity

Assessment:

Based on known data a significant mutagenic potential may be excluded.

Product details:

Result/Effect	Species/Test system	Source
negative	mutation assay (in vitro) bacterial cells	Conclusion by analogy OECD 471

11.1.6 Carcinogenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.7 Reproductive toxicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.8 Specific target organ toxicity (single exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.9 Specific target organ toxicity (repeated exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.10 Aspiration hazard

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.11 Further toxicological information

Other information: Human patch test: Product displays good compatibility with the skin.

12. Ecological information

12.1 Toxicity

Assessment:

No expected damaging effects to aquatic organisms. According to current knowledge adverse effects on water purification plants are not expected.

Product details:

Result/Effect	Species/Test system	Source
---------------	---------------------	--------

Material Safety Data Sheet

Material: 60002680

WACKER® AK 35
SILICONE FLUID

Version: 1.2 (US)

Date of print: 01/25/2013

Date of last alteration: 12/20/2012

0.0001 mg/l (measured) effect level > maximum achievable concentration	static (water-accommodated fraction) Daphnia magna (48 h)	literature (Polydimethylsiloxane)
IC ₅₀ (growth rate): > 100000 mg/l (nominal)	Marine alga (skeleonema costatum) (72 h)	literature (Polydimethylsiloxane)
NOEC (chronic): > 10000 mg/kg	feeding study rainbow trout (Oncorhynchus mykiss) (28 d)	literature (Polydimethylsiloxane)

12.2 Persistence and degradability

Assessment:

Biologically not degradable. Absorbed by floating particles. Separation by sedimentation. Polydimethylsiloxanes are degradable to a certain extent in abiotic processes.

12.3 Bioaccumulative potential

Assessment:

Polymer component: Bioaccumulation is not expected to occur.

12.4 Mobility in soil

Assessment:

Polymer component: Insoluble in water. Forms thin oil film on surface of water. Absorbed by floating particles. Separation by sedimentation.

12.5 Other adverse effects

none known

13. Disposal considerations

13.1 Product disposal

Recommendation:

Material that cannot be used or chemically reprocessed should be disposed of at an approved facility in accordance with any applicable governmental regulations.

13.2 Packaging disposal

Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations.

14. Transport information

14.1 US DOT & CANADA TDG SURFACE

Valuation: Not regulated for transport

14.2 Transport by sea IMDG-Code

Valuation: Not regulated for transport

14.3 Air transport ICAO-TI/IATA-DGR

Valuation: Not regulated for transport

15. Regulatory information

15.1 U.S. Federal regulations

TSCA inventory status and TSCA information:

This material or its components are listed on or are in compliance with the requirements of the TSCA Chemical Substance Inventory.

Material Safety Data Sheet

Material: 60002680

WACKER® AK 35
SILICONE FLUID

Version: 1.2 (US)

Date of print: 01/25/2013

Date of last alteration: 12/20/2012

TSCA 12(b) Export Notification:

This material does not contain any TSCA 12(b) regulated chemicals.

CERCLA Regulated Chemicals:

This material does not contain any CERCLA regulated chemicals.

SARA 302 EHS Chemicals:

This material does not contain any SARA extremely hazardous substances.

SARA 311/312 Hazard Class:

This product does not present any SARA 311/312 hazards.

SARA 313 Chemicals:

This material does not contain any SARA 313 chemicals above de minimus levels.

HAPS (Hazardous Air Pollutants):

This material does not contain any hazardous air pollutants.

15.2 U.S. State regulations**California Proposition 65 Carcinogens:**

This material does not contain any chemicals known to the state of California to cause cancer.

California Proposition 65 Reproductive Toxins:

This material does not contain any chemicals known to the state of California to cause reproductive effects.

Massachusetts Substance List:

This material contains no listed components.

New Jersey Right-to-Know Hazardous Substance List:

This material contains no listed components.

Pennsylvania Right-to-Know Hazardous Substance List:

This material contains no listed components.

15.3 Canadian regulations

This product has been classified in accordance with the Hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS Hazard Classes:

D2A

DSL Status:

This material or its components are listed on the Canadian Domestic Substances List.

Canadian Ingredient Disclosure List:

This material contains no listed components.

15.4 Other international regulations**EU Risk Phrases:**

R-Phrase	Description
R-	-

EU Safety Phrases:

S-Phrase	Description
S-	-

Details of international registration status

Listed on or in accordance with the following inventories:

EINECS - Europe
ECL - Korea
ENCS - Japan
AICS - Australia
IECSC - China
DSL - Canada
PICCS - Philippines

Material Safety Data Sheet

Material: 60002680

WACKER® AK 35
SILICONE FLUID

Version: 1.2 (US)

Date of print: 01/25/2013

Date of last alteration: 12/20/2012

TSCA - USA

16. Other information

16.1 Additional information:

This Material Safety Data Sheet (MSDS) meets the requirements of the Federal OSHA Hazard Communication Standard (29 CFR 1910.1200). This product has been classified according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR. This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee expressed or implied, is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license under valid patents. This MSDS provides selected regulatory information on this product, including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used.

Vertical lines in the left-hand margin indicate changes compared with the previous version.

All deliveries are subject to the WACKER SILICONES Health Care Policy, which is available at www.wacker.com.

16.2 Glossary of Terms:

ACGIH - American Conference of Governmental Industrial Hygienists
DOT - Department of Transportation
hPa - Hectopascals
mPa*s - Milli Pascal-Seconds
OSHA - Occupational Safety and Health Administration
PEL - Permissible Exposure Limit

ppm - Parts per Million
SARA - Superfund Amendments and Reauthorization Act
STEL - Short Term Exposure Limit
TSCA - Toxic Substances Control Act
TWA - Time Weighted Average
WHMIS - Canadian Workplace Hazardous Materials Identification System

Flash point determination methods

ASTM D56.....	Common name
ASTM D92, DIN 51376, ISO 2592	Tagliabue (Tag) closed cup
ASTM D93, DIN 51758, ISO 2719	Cleveland open cup
ASTM D3278, DIN 55680, ISO 3679	Pensky-Martens closed cup
DIN 51755	Setaflash or Rapid closed cup
	Abel-Pensky closed cup

16.3 Conversion table:

Pressure:.....: 1 hPa * 0.75 = 1 mm Hg = 1 torr; 1 bar = 1000 hPa
Viscosity:.....: 1 mPa*s = 1 centipoise (cP)